


GlacialTech Inc.
 http://www.glaciallight.com
 7F, No.352, Sec. 2, Zhongshan Rd., Zhonghe Dist., New Taipei City, Taiwan,
 235, R.O.C.

Operator GlacialLight R&D Department
 Telephone +886 2 2244-1227
 Fax +886 2 2244-1228
 e-Mail sales@GlacialLight.com

GlacialLight GL-BL300-NW-4000K-120D Lens(argyle)-no lampshade / Luminaire Data Sheet

Luminous emittance 1:

See our luminaire catalog for an image of the luminaire.



Luminaire classification according to CIE: 100
 CIE flux code: 49 88 99 100 108

Luminous emittance 1:


Glare Evaluation According to UGR											
ρ Ceiling	70	70	50	30	70	70	50	30	30	30	
ρ Walls	50	30	50	30	30	50	30	50	30	30	
ρ Floor	20	20	20	20	20	20	20	20	20	20	
Room Size X Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis					
2H	2H	27.3	28.5	27.5	28.8	29.0	27.7	29.0	28.0	29.2	29.4
	3H	27.5	28.6	27.8	28.9	29.1	28.0	29.1	28.3	29.4	29.6
	4H	27.4	28.5	27.7	28.7	29.0	27.9	29.0	28.3	29.3	29.6
	6H	27.3	28.3	27.7	28.6	28.9	27.9	28.8	28.2	29.1	29.5
	8H	27.3	28.2	27.6	28.5	28.9	27.8	28.8	28.2	29.1	29.4
4H	12H	27.2	28.1	27.6	28.5	28.8	27.8	28.7	28.2	29.0	29.3
	2H	27.6	28.7	27.9	28.9	29.2	28.0	29.0	28.3	29.3	29.6
	3H	27.8	28.7	28.2	29.1	29.4	28.3	29.2	28.7	29.5	29.8
	4H	27.8	28.6	28.2	28.9	29.3	28.3	29.1	28.7	29.4	29.8
	6H	27.7	28.4	28.2	28.8	29.2	28.2	28.9	28.6	29.3	29.7
8H	8H	27.7	28.3	28.1	28.7	29.1	28.2	28.8	28.6	29.2	29.6
	12H	27.7	28.2	28.1	28.6	29.1	28.1	28.7	28.6	29.1	29.5
	4H	27.7	28.4	28.2	28.7	29.2	28.2	28.8	28.6	29.2	29.6
	6H	27.7	28.2	28.1	28.6	29.1	28.1	28.6	28.6	29.1	29.5
	8H	27.6	28.1	28.1	28.5	29.0	28.1	28.5	28.6	29.0	29.5
12H	12H	27.6	28.0	28.1	28.4	28.9	28.1	28.5	28.6	28.9	29.4
	4H	27.7	28.3	28.1	28.7	29.1	28.2	28.7	28.6	29.1	29.6
	6H	27.6	28.1	28.1	28.5	29.0	28.1	28.5	28.6	29.0	29.5
	8H	27.6	28.0	28.1	28.4	28.9	28.1	28.4	28.6	29.0	29.4
	8H	27.6	28.0	28.1	28.4	28.9	28.1	28.4	28.6	28.9	29.4
Variation of the observer position for the luminaire distances S											
S = 1.0H	+0.3 / -0.5					+0.3 / -0.4					
S = 1.5H	+1.1 / -2.2					+0.9 / -1.6					
S = 2.0H	+2.1 / -5.2					+2.0 / -4.7					
Standard table	BK01					BK01					
Correction Summand	10.1					10.5					
Corrected Glare Indices referring to 34500lm Total Luminous Flux											

GlacialTech Inc.
<http://www.glaciallight.com>
7F, No.352, Sec. 2, Zhongshan Rd., Zhonghe Dist., New Taipei City, Taiwan,
235, R.O.C.

Operator GlacialLight R&D Department
Telephone +886 2 2244-1227
Fax +886 2 2244-1228
e-Mail sales@GlacialLight.com

GlacialLight GL-BL300-NW-4000K-120D Lens(argyle)-no lampshade / LDC (Polar)

Luminaire: GlacialLight GL-BL300-NW-4000K-120D Lens(argyle)-no lampshade
Lamps: 1 x Bay Light




GlacialTech Inc.
<http://www.glaciallight.com>
7F, No.352, Sec. 2, Zhongshan Rd., Zhonghe Dist., New Taipei City, Taiwan,
235, R.O.C.

Operator GlacialLight R&D Department
Telephone +886 2 2244-1227
Fax +886 2 2244-1228
e-Mail sales@GlacialLight.com

GlacialLight GL-BL300-NW-4000K-120D Lens(argyle)-no lampshade / LDC (Linear)

Luminaire: GlacialLight GL-BL300-NW-4000K-120D Lens(argyle)-no lampshade
Lamps: 1 x Bay Light



GlacialTech Inc.
 http://www.glaciallight.com
 7F, No.352, Sec. 2, Zhongshan Rd., Zhonghe Dist., New Taipei City, Taiwan,
 235, R.O.C.

Operator GlacialLight R&D Department
 Telephone +886 2 2244-1227
 Fax +886 2 2244-1228
 e-Mail sales@GlacialLight.com

GlacialLight GL-BL300-NW-4000K-120D Lens(argyle)-no lampshade / UGR-Table

Luminaire: GlacialLight GL-BL300-NW-4000K-120D Lens(argyle)-no lampshade

Lamps: 1 x Bay Light

Glare Evaluation According to UGR											
ρ Ceiling	70	70	50	50	30	70	70	50	50	30	
ρ Walls	50	30	50	30	30	50	30	50	30	30	
ρ Floor	20	20	20	20	20	20	20	20	20	20	
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	27.3	28.5	27.5	28.8	29.0	27.7	29.0	28.0	29.2	29.4
	3H	27.5	28.6	27.8	28.9	29.1	28.0	29.1	28.3	29.4	29.6
	4H	27.4	28.5	27.7	28.7	29.0	27.9	29.0	28.3	29.3	29.6
	6H	27.3	28.3	27.7	28.6	28.9	27.9	28.8	28.2	29.1	29.5
	8H	27.3	28.2	27.6	28.5	28.9	27.8	28.8	28.2	29.1	29.4
	12H	27.2	28.1	27.6	28.5	28.8	27.8	28.7	28.2	29.0	29.3
4H	2H	27.6	28.7	27.9	28.9	29.2	28.0	29.0	28.3	29.3	29.6
	3H	27.8	28.7	28.2	29.1	29.4	28.3	29.2	28.7	29.5	29.8
	4H	27.8	28.6	28.2	28.9	29.3	28.3	29.1	28.7	29.4	29.8
	6H	27.7	28.4	28.2	28.8	29.2	28.2	28.9	28.6	29.3	29.7
	8H	27.7	28.3	28.1	28.7	29.1	28.2	28.8	28.6	29.2	29.6
	12H	27.7	28.2	28.1	28.6	29.1	28.1	28.7	28.6	29.1	29.5
8H	4H	27.7	28.4	28.2	28.7	29.2	28.2	28.8	28.6	29.2	29.6
	6H	27.7	28.2	28.1	28.6	29.1	28.1	28.6	28.6	29.1	29.5
	8H	27.6	28.1	28.1	28.5	29.0	28.1	28.5	28.6	29.0	29.5
	12H	27.6	28.0	28.1	28.4	28.9	28.1	28.5	28.6	28.9	29.4
12H	4H	27.7	28.3	28.1	28.7	29.1	28.2	28.7	28.6	29.1	29.6
	6H	27.6	28.1	28.1	28.5	29.0	28.1	28.5	28.6	29.0	29.5
	8H	27.6	28.0	28.1	28.4	28.9	28.1	28.4	28.6	28.9	29.4
Variation of the observer position for the luminaire distances S											
S = 1.0H	+0.3 / -0.5					+0.3 / -0.4					
S = 1.5H	+1.1 / -2.2					+0.9 / -1.6					
S = 2.0H	+2.1 / -5.2					+2.0 / -4.7					
Standard table	BK01					BK01					
Correction Summand	10.1					10.5					
Corrected Glare Indices referring to 34500lm Total Luminous Flux											

The UGR values have been calculated according to CIE Publ. 117 Spacing-to-Height-Ratio = 0.25.

GlacialTech Inc.
 http://www.glaciallight.com
 7F, No.352, Sec. 2, Zhongshan Rd., Zhonghe Dist., New Taipei City, Taiwan,
 235, R.O.C.

Operator GlacialLight R&D Department
 Telephone +886 2 2244-1227
 Fax +886 2 2244-1228
 e-Mail sales@GlacialLight.com

GlacialLight GL-BL300-NW-4000K-120D Lens(argyle)-no lampshade / Glare Data Sheet

Luminaire: GlacialLight GL-BL300-NW-4000K-120D Lens(argyle)-no lampshade

Lamps: 1 x Bay Light

Glare Evaluation According to UGR											
ρ Ceiling	70	70	50	50	30	70	70	50	50	30	
ρ Walls	50	30	50	30	30	50	30	50	30	30	
ρ Floor	20	20	20	20	20	20	20	20	20	20	
Room Size X Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis					
2H	2H	27.3	28.5	27.5	28.8	29.0	27.7	29.0	28.0	29.2	29.4
	3H	27.5	28.6	27.8	28.9	29.1	28.0	29.1	28.3	29.4	29.6
	4H	27.4	28.5	27.7	28.7	29.0	27.9	29.0	28.3	29.3	29.6
	6H	27.3	28.3	27.7	28.6	28.9	27.9	28.8	28.2	29.1	29.5
	8H	27.3	28.2	27.6	28.5	28.9	27.8	28.8	28.2	29.1	29.4
	12H	27.2	28.1	27.6	28.5	28.8	27.8	28.7	28.2	29.0	29.3
4H	2H	27.6	28.7	27.9	28.9	29.2	28.0	29.0	28.3	29.3	29.6
	3H	27.8	28.7	28.2	29.1	29.4	28.3	29.2	28.7	29.5	29.8
	4H	27.8	28.6	28.2	28.9	29.3	28.3	29.1	28.7	29.4	29.8
	6H	27.7	28.4	28.2	28.8	29.2	28.2	28.9	28.6	29.3	29.7
	8H	27.7	28.3	28.1	28.7	29.1	28.2	28.8	28.6	29.2	29.6
	12H	27.7	28.2	28.1	28.6	29.1	28.1	28.7	28.6	29.1	29.5
8H	4H	27.7	28.4	28.2	28.7	29.2	28.2	28.8	28.6	29.2	29.6
	6H	27.7	28.2	28.1	28.6	29.1	28.1	28.6	28.6	29.1	29.5
	8H	27.6	28.1	28.1	28.5	29.0	28.1	28.5	28.6	29.0	29.5
	12H	27.6	28.0	28.1	28.4	28.9	28.1	28.5	28.6	28.9	29.4
12H	4H	27.7	28.3	28.1	28.7	29.1	28.2	28.7	28.6	29.1	29.6
	6H	27.6	28.1	28.1	28.5	29.0	28.1	28.5	28.6	29.0	29.5
	8H	27.6	28.0	28.1	28.4	28.9	28.1	28.4	28.6	28.9	29.4
Variation of the observer position for the luminaire distances S											
S = 1.0H	+0.3 / -0.5					+0.3 / -0.4					
S = 1.5H	+1.1 / -2.2					+0.9 / -1.6					
S = 2.0H	+2.1 / -5.2					+2.0 / -4.7					
Standard table Correction Summand	BK01 10.1					BK01 10.5					
Corrected Glare Indices referring to 34500lm Total Luminous Flux											

The UGR values have been calculated according to CIE Publ. 117 Spacing-to-Height-Ratio = 0.25.

